How to Enable Mailu API

Mailu · https://wpemailmanager.com/docs/how-to-enable-mailu-api/

Ensure that you have installed the *master* branch of Mailu, then do the following:

1. SSH to your server as root and proceed to the mailu directory. By default it is *mailu*
   `cd /mailu`
2. Shutdown the Mailu docker instance if it is running by running the command:
   `docker-compose -p mailu down`
3. Edit the *mailu.env* file using your editor of choice. For this case, we will use *nano*
   `nano mailu.env`
4. Add the following constants if they are not present:
   `API=true`
   `WEB_API=/api`
   `API_TOKEN:your_api_token`
   Replace *your_api_token*, with a hard to guess api token. You can generate one here. This api token will be used when configuring the plugin's general settings.

   The end should result should be similar to one below.

   ```
   # API
   API=true
   API_TOKEN=Lm/RN2//Si0rbsvXBgLlGsar-hdKKTHz!tw17EdChNItVQhr9cREUlCWhG24?J!K
   WEB_API=/api
   ```

   Save the changes made.
5. Restart the Mailu docker instance by running the following command:
   docker-compose -p mailu up -d
6. Ensure that the API is running by going to *https://yourserver.com/api/v1*. You should see a result similar to one below.

Mailu API 1.0

[Base URL: /api/v1]

/api/v1/swagger.json

Authorize

user User operations

GET	/user	List users	list_users
POST	/user	Create user	create_user
GET	/user/{email}	Find user	find_user
DELETE	/user/{email}	Delete user	delete_user
PATCH	/user/{email}	Update user	update_user

domain Domain operations